

### P6-TWC

### SPEC SHEET



**DESCRIPTION:** The offset segment design of the P6-TWC creates a 30mm wide channel for the installation of conduit and pipework in popular construction materials, significantly reducing the need to chisel the centre of the chase. When used in conjunction with an appropriate dust extraction system (minimum of 'M-Class'), it can dramatically reduce the amount of airborne dust and clearing up.

**FEATURES:** 10mm high diamond segments, reduces workload and improves the working environment (when used with dust extraction).

**MACHINE SUITABILITY:** Suitable for 125mm wall chasing machines, including the Metabo MFE40.

**STANDARDS:**


- EN13236: European Standard that regulates the safety requirements for super abrasive (diamond) products.

**USER TIPS:**

- Make certain the blade is suitable for the material before cutting
- Always cut a straightline, do not attempt to change direction whilst cutting
- In harder materials, it is advisable to cut the channel in two stages, going half depth on the first pass, before completing the cut at full depth. This will greatly reduce the load on the machine
- Wall chasing creates a large amount of airborne dust. It is strongly advised that a dust extraction unit is used with a minimum specification of 'M-Class'. This in addition to wearing the full and appropriate PPE.

**PACKAGING DETAILS:**

White corrugated cardboard box.



**PRODUCT DETAILS:**

**Part No. Dimensions**

**DP19120** 125mm x 28.5mm x 22.2mm (5")

IDEALLY SUITED OCCASIONAL USE

MATERIAL	
ALUMINIUM	
ASPHALT	
ASPHALT OVER CONCRETE	
BRICKS - CLASS A ENGINEERING	
BRICKS - CLASS B ENGINEERING	
BRICKS - STANDARD FACING BRICKS	
CEMENT FIBRE BOARD	
CAST IRON	
CLAY PRODUCTS	
COMPOSITE CLADDING & PANELS	
CONCRETE - BEAMS, KERBS, PIPES & SLABS	
CONCRETE - BLOCK PAVING	
CONCRETE - FLAG STONES	
CONCRETE - FLINT AGGREGATE	
CONCRETE - GENERAL PURPOSE	
CONCRETE - GREEN (up to 24 Hours Old)	
CONCRETE - HEAVY STEEL REINFORCEMENT	
CONCRETE - LIGHT STEEL REINFORCEMENT	
CONCRETE - ROOF TILES	
CONCRETE BLOCKS - LIGHTWEIGHT 3 TO 7 NEWTON	
CONCRETE BLOCKS - MEDIUM DENSITY 7 TO 12 NEWTON	
CONCRETE BLOCKS - SOLID DENSITY 12+ NEWTON	
CEMENT SCREED	
EARTHSTONE WORKTOPS	
FIBREGLASS	
GLASS REINFORCED PLASTIC (GRP)	
GRANITE - BLOCKS & WORKTOPS	
GRITSTONE	
GROUNDWORK - HARD SOIL	
LAMINATED PRODUCTS	
LIMESTONE	
MARBLE - BLOCKS & WORKTOP	
MORTAR RAKING	
PE POLYETHYLENE PLASTIC	
PP POLYPROPYLENE PLASTIC	
QUARTZ WORKTOPS	
RUBBER	
RAILWAY SLEEPERS	
SANDSTONE - ABRASIVE	
SANDSTONE - INDIAN	
STAINLESS STEEL (INOX)	
STEEL SECTION - PIPES & BARS	
TILES - CERAMIC	
TILES - GRANITE	
TILES - LIMESTONE	
TILES - MARBLE	
TILES - PORCELAIN	
TILES - SLATE	
TREE ROOTS	
WOOD	
YORK STONE	

E sales@premierdiamondproducts.co.uk T +44 (0) 1227 711 555

